CEILING 40/10
E-40C/E-10C

Specifications

Light Source: 1 x 36W cool/warm white LED (E-40C)
1 x 12W cool/warm white LED (E-10C)
Color Temperature: 3200±150K/5600±150K (optional)
Beam Angle: 19°/26°/36°/50°

Photometrics Diagram

E-40C



19°Lux	CW	2920	730	322	180
	WW	2758	680	310	170
Diameter(m)	CW/WW	0.68	1.34	2.01	2.68
26°Lux	CW	1950	488	215	121
	WW	1842	461	205	115
Diameter(m)	CW/WW	0.94	1.85	2.78	3.70
36 °Lux	CW	1170	290	130	70
	WW	1010	250	112	62
Diameter(m)	CW/WW	1.31	2.59	3.91	5.19
50 °Lux	CW	596	150	66	37
	WW	517	130	56	32
Diameter(m)	CW/WW	1.87	3.73	5.59	7.46

E-10C



19°Lux	CW	2002	501	223	125
	WW	1898	475	211	120
Diameter(m)	CW/WW	0.68	1.34	2.01	2.68
26°Lux	CW	1095	274	122	68
	WW	981	246	109	62
Diameter(m)	CW/WW	0.94	1.85	2.78	3.70
36°Lux	CW	540	135	60	33
	WW	415	103	46	25
Diameter(m)	CW/WW	1.31	2.59	3.91	5.19
50°Lux	CW	310	77	34	19
	WW	212	53	23	13
Diameter(m)	CW/WW	1.87	3.73	5.59	7.46

Dimensions(mm)



Construction

Power Socket: Power cord out
Protection Rating: IP20

Optical

CRI: WW≥95, CW≥95
CQS: WW≥95, CW≥95
TLCI: WW≥95, CW≥95

Electrical and Physical

Power Voltage: AC 85~127V, 50/60Hz,
AC 175~264V, 50/60Hz
Power Consumption: 24W (E-40C)/17W (E-10C)
Dimension(mm): 273x128x100mm,
1.5Kg(E-40C(/1.3Kg(E-10C)
Dimension(in): 10.7"x5.0"x3.9"in,
3.3lbs(E-40C)/2.8lbs(E-10C)

Features

E-40C/ E-10C is Ceiling Version, uniform light, sharp image edge,and self-locking focus lens. The product takes advantage of the heat pipe heat conduction and housing feature to dissipate heat without a fan to prolong LED life.